




Weasler®

50° CV DRIVE SHAFT LUBRICATING PROCEDURE

SERVICE INSTRUCTIONS



LUBRICATE ALL FITTINGS WITH A GOOD QUALITY LITHIUM SOAP COMPATIBLE E.P. GREASE MEETING THE N.L.G.I. #2 SPECIFICATIONS AND CONTAINING NO MORE THAN 1% MOLYBDENUM DISULFIDE.

AN E.P. GREASE MEETING THE N.L.G.I. #2 SPECIFICATIONS AND CONTAINING 3% MOLYBDENUM DISULFIDE MAY BE SUBSTITUTED IN THE TELESCOPING MEMBERS ONLY.



LOCATION	STANDARD INTERVAL	EXTENDED LUBE INTERVAL	LEVER ACTION PUMPS
CROSS & BEARINGS	*8 HRS.	50 HRS.	5
TELESCOPING MEMBERS	8 HRS.	50 HRS.	8-10
CV BALL & SOCKET	*8 HRS.	N/A	5
CE & NON-ROTATING GUARD BUSHINGS (1000 RPM MAX.)	8 HRS.	50 HRS.	5

*CONSTANT ANGLE APPLICATIONS MAY REQUIRE A LUBE INTERVAL OF 4 HOURS

ROTATING GUARD BUSHINGS SHOULD BE LUBRICATED UPON REPLACEMENT

CAUTION!! REPLACEMENT PARTS ARE NOT LUBRICATED

REPLACEMENT PARTS MUST BE LUBRICATED AT TIME OF ASSEMBLY AND DURING USE PER THE LUBE RECOMMENDATIONS

UNCONTROLLED DOCUMENT 56-15145-07

Weasler Engineering, Inc.
 P.O. Box 558, West Bend, WI 53095 USA
 Tel: +1-262.338.2161, Fax: +1-262.338.3709
 E-mail: oemsales@weasler.com
 web site: www.weasler.com

Weasler Engineering BV
 P.O. Box 266, 6600 AG, Wijchen, The Netherlands
 Tel: +31 (0)24 64 89 100, Fax: +31 (0)24 64 89 109
 E-mail: sales@weasler.nl
 web site: www.weasler.com

Weasler Engineering Kft
 P.O. Box 262, H6001, Kecskemet, Hungary
 Tel: +36 (0)76 500 410, Fax: +36 (0)76 500 415
 E-mail: sales@weasler.nl
 web site: www.weasler.com