




# Weasler®

# 50° CV DRIVE SHAFT LUBRICATING PROCEDURE

## SERVICE INSTRUCTIONS



LUBRICATE ALL FITTINGS WITH A GOOD QUALITY LITHIUM SOAP COMPATIBLE E.P. GREASE MEETING THE N.L.G.I. #2 SPECIFICATIONS AND CONTAINING NO MORE THAN 1% MOLYBDENUM DISULFIDE.

AN E.P. GREASE MEETING THE N.L.G.I. #2 SPECIFICATIONS AND CONTAINING 3% MOLYBDENUM DISULFIDE MAY BE SUBSTITUTED IN THE TELESCOPING MEMBERS ONLY.



LOCATION	STANDARD INTERVAL	EXTENDED LUBE INTERVAL	LEVER ACTION PUMPS
CROSS & BEARINGS	8 HRS.	50 HRS.	5
TELESCOPING MEMBERS	8 HRS.	50 HRS.	8-10
CV BALL & SOCKET	*8 HRS.	* 8 HRS.	5
CE & NON-ROTATING GUARD BUSHINGS (1000 RPM MAX.)	8 HRS.	50 HRS.	5

*\*CONSTANT ANGLE APPLICATIONS MAY REQUIRE A LUBE INTERVAL OF 4 HOURS*

ROTATING GUARD BUSHINGS SHOULD BE LUBRICATED UPON REPLACEMENT

**CAUTION!! REPLACEMENT PARTS ARE NOT LUBRICATED**

*REPLACEMENT PARTS MUST BE LUBRICATED AT TIME OF ASSEMBLY AND DURING USE PER THE LUBE RECOMMENDATIONS*

UNCONTROLLED DOCUMENT 56-15145-08

Weasler Engineering, Inc.  
 P.O. Box 558, West Bend, WI 53095 USA  
 Tel: +1-262.338.2161, Fax: +1-262.338.3709  
 E-mail: oemsales@weasler.com  
 web site: www.weasler.com

Weasler Engineering BV  
 Bijsterhuizen 3031, 6604 LP, Wijchen, The Netherlands  
 Tel: +31 (0)24 64 89 100, Fax: +31 (0)24 64 89 109  
 E-mail: sales@weasler.nl  
 web site: www.weasler.com

Weasler Engineering Kft  
 P.O. Box 262, H6001, Kecskemet, Hungary  
 Tel: +36 (0)76 500 410, Fax: +36 (0)76 500 415  
 E-mail: sales@weasler.nl  
 web site: www.weasler.com